



Specifications Ledvance LED Panel  
Linear Indiviled Direct 1200 40W  
4000lm - 940 Cool White | 120x12cm -  
UGR <19 - Dali Dimmable

[View Product](#)

General Information

|                          |                                                                       |
|--------------------------|-----------------------------------------------------------------------|
| SKU                      | 256357                                                                |
| EAN                      | 4099854591679                                                         |
| Brand                    | Ledvance                                                              |
| Manufacturer Name        | LINEAR INDIVILED DIRECT 1200 DALI ASYMMETRIC 1200 P 40W 940 DA ASY BK |
| Any Lamp all-in warranty | 5 Years                                                               |
| Average Lifetime (h)     | 100000                                                                |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x36               |
| Wattage                     | 40                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 940 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 90-99              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 4000               |
| Luminous Efficacy (lm/W)    | 100                |

|                        |                |
|------------------------|----------------|
| IP-rating              | IP20           |
| Impact Protection (IK) | IK06 - 1 joule |
| Power factor           | >0.90          |
| Product Type Category  | LED Panel      |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Ceiling                        |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | Plastic                        |
| Operating Temperature | -20 to +50                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | Black                          |
| Housing               | Aluminium                      |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x12cm |
| Length (mm)    | 1210     |
| Width (mm)     | 125      |
| Height (mm)    | 43       |

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

**Why Any-lamp?**



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

